

ET-WMP2DS

Dual Streaming 2.0 Megapixel Wireless Network Video Server



Key Features



- * High Quality 2.0 Megapixel CMOS Image Sensor
- * Wireless G / IEEE 802.11 b/g WLAN
- * 30 FPS at D1 Resolution
- * Supports Simultaneous Connection for up to 50 Users
- * Power Over Ethernet (PoE)
- * Full Duplex Two Way Audio
- * Supports DDNS

ET-WMP2DS Specifications

Wireless	Wireless G / IEEE 802.11 b/g Wireless LAN
Image Sensor	2.0 Megapixel CMOS Sensor
Network Connection	10 / 100 Base-Tx RJ-45 Ethernet Connection
Compression	MPEG4 / JPEG
Video Resolution	720x480, 640x480, 320x240
Minimum Illumination	0.5 Lux
Buffer Rate	200 Frames (320x240) at Max with Time Display
Audio Communication	2-Way Full Duplex
Audio Bandwidth	300Hz - 3.4 KHz
Audio Input / Output	1/8" 3.5mm Mini Jack / Stereo
Frame Rate	30fps @ D1 Resolution
Pan / Tilt / Zoom	Digital 5x Zoom & Pan Tilt Operation
Protocols	TCP/IP, UDP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3
Image Transfer Methods	Alarm Trigger or Timer
LED	Power / Network Communication / Camera Operation
Power	AC Adapter: 120V AC Input / 60Hz Output 750mA 12V DC
Operating Temperature	32 ~ 122 Fahrenheit
Storage Temperature	32 ~ 122 Fahrenheit
Operating Humidity	20 ~ 80% Non Condensing
Storage Humidity	20 ~ 90% Non Condensing
Dimensions	3.5" (W) x 1.6" (H) x 6.1" (L)
Net Weight	0.6 lbs.