

# EVSS-DAS-3U16S

3U Rackmount 16 Bay RAID 6 / JBOD DAS Server



## Features

**SATA I & II type HDD Compatibility**

**Multi-Layered Power Conversion: AC to DC & DC to DC for eliminating the chances of disk bad sectors by allowing the power input to fluctuate**

**Embedded enclosure management through LCD control panel**

**Online RAID management via RS-232 or Ethernet.**

**Intuitive and comprehensive GUI for configuration and monitoring from remote and local**

## Specifications

Form Factor	3U Rackmount Chassis
HDD Bays	16 Hot-Swappable 3.5"
RAID Level	0, 1, 0+1, 3, 5, 6 & JBOD
Maximum Capacity	16TB
Auto Rebuilding	Yes
Hot-Spare	RAID 3, 5, 6
Host Interface & Transfer Rate	Dual SCSI Ultra320 (320Mbps)
Drive Interface	SATA II
Power Supply	400W x 1 + 1 Redundant Optional 3 <sup>rd</sup> or 4 <sup>th</sup> Hot Swap Power
Control Interface	LCD Panel, RS232, RJ-45
Status Indicators	1 LED / HDD
Dimensions	5.5" H x 19" W x 22.75" D
Weight	56 lbs. (not including HDDs)



**Eastman Security**

**Eastman Telebell International Inc.**

15358 E. Valley Blvd., City of Industry, CA 91746

Tel : 1-800-526-7777 | Fax : 1-626-336-1939

[www.eastmansecurity.com](http://www.eastmansecurity.com)

© 2007, Eastman Telebell International Inc. All rights reserved.

\* Model and specifications are subject to change without notice.

\* All non-metric weights and measures are approximate.

EVR-062107-B