

LCD MONITOR SPECIFICATION

Resolution	1024 x 768
Luminance	450
Contrast Ratio	600: 1

DVR SPECIFICATION

CPU	32bit DSP
HDD	1 Internal IDE Drive
Operating System	RTOS
Video Input	Composite Video: RJ45 x 4 or BNC x 4
Video Output	Composite Video: BNC x 1
Audio Input	4 RCA Inputs
Audio Output	1 Speaker Output
P/T/Z Control & Port	Built-In RS-485
Network Connectivity	10/100 Base Tx
System Operation	Front Panel Buttons or IR Remote Controller
Screen Modes	1 & 4 Channel Partition Mode Auto Switching Mode
Compression	MPEG4 (Modified)
Recording Resolutions	352 x 240 / 704 x 240 / 704 x 480
Recording Speed	120 IPS@352 x 240 60 IPS@704 x 240 30 IPS@704 x 480
File Size Per Image	3~5 KB @ 352 x 240 5~10 KB @ 704 x 240 6~16 KB @ 704 x 480
Recording Modes	Continuous, Motion Detection & Sensor Activation
Recording Schedule	Adjustable Schedule Per Camera
Motion Detection	Adjustable Sensitivity Per Camera
Remote Transmission	Remote Live Viewing, Playback & Recording (Triplex Operation)
System Recovery After Power Failure	Auto-Rebooting, Auto-Scan and Recovery for Data
Data Backup	1 USB Port
Storage Temp & Humidity	-68~149 Fahrenheit / 20~80%RH
Operating Temp & Humidity	-41~104 Fahrenheit / 20~80%RH
Power	DC12V
Dimensions	13.7" (W) x 12.4" (H) x 2.5" (D) Inches
Weight	18.7 lbs.



*LVR-812: 8 Ch available



Eastman Security

Eastman Telebell International Inc.

15358 E. Valley Blvd., City of Industry, CA 91746
Tel : 1-800-526-7777 | Fax : 1-626-336-1939

www.eastmansecurity.com

© 2008, Eastman Telebell International Inc. All rights reserved.
* Model and specifications are subject to change without notice.
* All non-metric weights and measures are approximate.

LVR412-012208-D